U.S. Application No. 09/760,843 Docket No. 2091-0230P Supplemental Reply filed September 26, 2005 Page 2 of 13

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (PREVIOUSLY PRESENTED) A method of controlling image data transfer between a server storing image data and a client connected to the server via a network and receiving the image data by accessing the server, the image-data transfer control method comprising the steps of:

measuring a transfer rate of the network at the time the client requests transfer of image data sets from the server;

determining the number of the image data sets to be sent to the client in response to the transfer request, based on the transfer rate and a permitted transfer time determined in advance; and

transferring to the client a message notifying that the number of the image data sets to be transferred is 0 in the case where the number of the image data sets to be transferred has been determined to be 0.

- 2. (ORIGINAL) An image-data transfer control method as defined in Claim 1, further comprising the step of transferring the image data sets whose number has been determined from the server to the client.
- 3. (ORIGINAL) An image-data transfer control method as defined in Claim 2, wherein the step of transferring is the step of transferring the image

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 3 of 13

data sets whose number has been determined from the server to the client,

based on priority of the image data sets whose transfer is requested.

4. (ORIGINAL) An image-data transfer control method as defined in

Claim 2, further comprising the step of transferring, from the server to the

client, low volume data sets of a remaining portion of the requested image data

sets excluding the image data sets whose transfer from the server to the client

has been determined.

5. (ORIGINAL) An image-data transfer control method as defined in

Claim 4, further comprising the step of transferring from the server to the

client, in the case where transfer of the image data sets corresponding to the

low volume data sets is requested, the image data sets corresponding to the low

volume data sets whose transfer is requested.

6. (CANCELED)

7. (ORIGINAL) An image-data transfer control method as defined in

any one of Claims 1 to 5, further comprising the step of transferring

information representing the transfer rate to the client.

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 4 of 13

8. (ORIGINAL) An image-data transfer control method as defined in

any one of Claims 1 to 5, wherein the image data sets are thumbnail image

data for displaying, on the client, thumbnail images comprising images

represented by the image data sets.

9. (PREVIOUSLY PRESENTED) An apparatus for controlling image

data transfer between a server storing image data and a client connected to the

server via a network and receiving the image data by accessing the server, the

image-data transfer control apparatus comprising:

means for measuring a transfer rate of the network at the time the client

requests transfer of image data sets from the server;

means for determining the number of the image data sets to be

transferred to the client in response to the transfer request, based on the

transfer rate and a permitted transfer time determined in advance; and

means for sending a message to the client notifying that the number of

the image data sets is 0 in the case where the number of the image data sets

has been determined to be 0.

10. (ORIGINAL) An image-data transfer control apparatus as defined in

Claim 9, further comprising means for transferring the image data sets whose

number has been determined from the server to the client.

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 5 of 13

11. (ORIGINAL) An image-data transfer control apparatus as defined in

Claim 10, wherein the means for transferring transfers the image data sets

whose number has been determined from the server to the client, based on

priority of the image data sets whose transfer is requested.

12. (ORIGINAL) An image-data transfer control apparatus as defined in

Claim 10, wherein the means for transferring transfers, from the server to the

client, low volume data sets of a remaining portion of the requested image data

sets excluding the image data sets whose transfer from the server to the client

has been determined.

13. (ORIGINAL) An image-data transfer control apparatus as defined in

Claim 12, wherein the means for transferring transfers, from the server to the

client, the image data sets corresponding to the low volume data sets when

transfer of the image data sets corresponding to the low volume data sets is

requested.

14. (CANCELED)

15. (ORIGINAL) An image-data transfer control apparatus as defined in

any one of Claims 9 to 13, further comprising means for transferring

information representing the transfer rate to the client.

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 6 of 13

16. (ORIGINAL) An image-data transfer control apparatus as defined in

any one of Claims 9 to 13, wherein the image data sets are thumbnail image

data for displaying, on the client, thumbnail images comprising images

represented by the image data sets.

17. (PREVIOUSLY PRESENTED) A computer-readable recording

medium storing a program to cause a computer to execute a method of

controlling image data transfer between a server storing image data and a

client connected to the server via a network and receiving the image data by

accessing the server, the program comprising the procedures of:

measuring a transfer rate of the network at the time the client requests

transfer of image data sets from the server;

determining the number of the image data sets to be sent to the client in

response to the transfer request, based on the transfer rate and a permitted

transfer time determined in advance; and

transferring to the client a message notifying that the number of the

image data sets to be transferred is 0 in the case where the number of the

image data sets to be transferred has been determined to be 0.

18. (ORIGINAL) A computer-readable recording medium as defined in

Claim 17, the program further comprising the procedure of transferring the

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 7 of 13

image data sets whose number has been determined from the server to the

client.

19. (ORIGINAL) A computer-readable recording medium as defined in

Claim 18, wherein the procedure of transferring is the procedure of transferring

the image data sets whose number has been determined from the server to the

client, based on priority of the image data sets whose transfer is requested.

20. (ORIGINAL) A computer-readable recording medium as defined in

Claim 18, the program further comprising the procedure of transferring, from

the server to the client, low volume data sets of a remaining portion of the

requested image data sets excluding the image data sets whose transfer from

the server to the client has been determined.

21. (ORIGINAL) A computer-readable recording medium as defined in

Claim 20, the program further comprising the procedure of transferring from

the server to the client, in the case where transfer of the image data sets

corresponding to the low volume data sets is requested, the image data sets

corresponding to the low volume data sets whose transfer is requested.

22. (CANCELED)

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 8 of 13

23. (ORIGINAL) A computer-readable recording medium as defined in

any one of Claims 17 to 21, the program further comprising the procedure of

transferring information representing the transfer rate to the client.

24. (ORIGINAL) A computer-readable recording medium as defined in

any one of Claims 17 to 21, wherein the image data sets are thumbnail image

data for displaying, on the client, thumbnail images comprising images

represented by the image data sets.

25. (PREVIOUSLY PRESENTED) An image-data transfer control

method as defined in Claim 1, wherein an amount of time necessary for

transferring the number of image data sets is approximately the permitted

transfer time.

26. (PREVIOUSLY PRESENTED) An image-data transfer control

apparatus as defined in Claim 9, wherein an amount of time necessary for

transferring the number of image data sets is approximately the permitted

transfer time.

27. (PREVIOUSLY PRESENTED) A computer-readable recording

medium as defined in Claim 17, wherein an amount of time necessary for

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 9 of 13

transferring the number of image data sets is approximately the permitted

transfer time.

28. (WITHDRAWN) A method of measuring a transfer rate of a network,

comprising:

transmitting from a server to a requesting client data of a predetermined

data size;

receiving a reply from the requesting client sent in response to the data

of the first predetermined size;

measuring a response time based on a start time in which the data of the

predetermined size was transmitted by the server and an end time in which the

reply was received from the requesting client; and

determining the transfer rate based on the predetermined data size and

the response time.

29. (WITHDRAWN) The method of claim 28, wherein the response time

is measured as a difference between the start and end times, and wherein the

transfer rate is determined by dividing the predetermined data size of data by

the response time.

30. (WITHDRAWN) The method of claim 28, wherein the predetermined

data size a first predetermined data size, the reply from the requesting client is

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 10 of 13

a first reply, the response time is a first response time, the start time is a first

start time, and the end time is a first end time, the method further comprising:

transmitting from the server to the requesting client data of a second

predetermined size;

receiving a second reply from the requesting client sent in response to

the data of the second predetermined size;

measuring a second response time based on a second start time in which

the data of the second predetermined size was transmitted by the server and a

second end time in which the second reply was received from the requesting

client; and

determining the transfer rate based on the first and second

predetermined data sizes and first and second response times.

31. (WITHDRAWN) The method of claim 30, wherein the first and

second predetermined sizes are not equal,

32. (WITHDRAWN) The method of claim 31, wherein

in the measuring step, the first response time is measured as a difference

between the first start and end times and the second response time is

measured as a difference between the second start and end times, and

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 11 of 13

in the determining the transfer rate step, the transfer rate is determined

by dividing a size difference between the first and second predetermined data

sizes by a time difference between the first and second response times.

33. (PREVIOUSLY PRESENTED) An image-data transfer control

method as defined in Claim 4, further comprising transferring from the server

to the client all non-transfer image data sets corresponding all low volume data

sets upon request from a user interfacing with the client.

34. (PREVIOUSLY PRESENTED) An image-data transfer control

method as defined in Claim 7, further comprising displaying a representation of

the transfer rate on a display of the client.

35. (PREVIOUSLY PRESENTED) A method of controlling image data

transfer between a server storing image data and a client connected to the

server via a network and receiving the image data by accessing the server, the

image-data transfer control method comprising the steps of:

receiving a requested number of image data sets for transfer from a

client;

measuring a transfer rate of the network at the time the client requests

transfer of image data sets from the server; and

Docket No. 2091-0230P

Supplemental Reply filed September 26, 2005

Page 12 of 13

determining an actual number of the image data sets to be sent to the

client in response to the transfer request based on the transfer rate and a

permitted transfer time determined in advance, wherein an actual number is

less than or equal to the requested number.

36. (NEW) An image-data transfer control method as defined in claim 3,

wherein the priority of the image data sets is set based on any one or more of

an order of file size, an order of image size, chronological order of image data

generation, chronological order of photographing, chronological order of last

access, and order of user preference.

37. (NEW) An image-data transfer control apparatus as defined in

claim 11, wherein the priority of the image data sets is set based on any one or

more of an order of file size, an order of image size, chronological order of image

data generation, chronological order of photographing, chronological order of

last access, and order of user preference.

38. (NEW) A computer-readable recording medium as defined in Claim

19, wherein the priority of the image data sets is set based on any one or more

of an order of file size, an order of image size, chronological order of image data

generation, chronological order of photographing, chronological order of last

access, and order of user preference.